

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE

SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 7, 8, 18, 19, 30, AND 31

IN

TOWNSHIP 12 SOUTH, RANGE 2 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

M. Ross Workman and Ronald K. Baugh
Supervisory Cadastral Surveyors

Under special instructions dated *September 6, 1996*, approved *September 6, 1996*, which provided for the surveys included under Group Number 857, and assignment instructions dated *September 9, 1996*.

Survey commenced *October 3, 1996*

Survey completed *November 4, 1996*

INDEX DIAGRAM

Township 12 South, Range 2 West

| | | | | | |
|----------------|-----------|----|----|----|----|
| 6 | 5 9 | 4 | 3 | 2 | 1 |
| 7 8 8 | 8 3 8 | 9 | 10 | 11 | 12 |
| 18 7 7 6 | 17 2 6 | 16 | 15 | 14 | 13 |
| 19 5 5 | 20 | 21 | 22 | 23 | 24 |
| 30 4 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |

| | |
|------------------------------------|---------|
| The Subdivision of Section 7..... | Page 10 |
| The Subdivision of Section 8..... | Page 11 |
| The Subdivision of Section 18..... | Page 13 |
| The Subdivision of Section 19..... | Page 15 |
| The Subdivision of Section 30..... | Page 17 |
| The Subdivision of Section 31..... | Page 19 |

TOWNSHIP 12 SOUTH, RANGE 2 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 7, 8, 18, 19, 30, and 31, of T. 12 S., R. 2 W., Salt Lake Meridian, Utah.

History of Surveys

| | Surveyed by | | Retr. or Resurveyed by | |
|-----------------------|---------------------|------|------------------------|------|
| NORTH BOUNDARY | | | | |
| Portion | J. Gorkinski | 1873 | Located 1 mile north | |
| All | A.J. Stewart, Jr. | 1878 | | |
| Portion | | | H.D. Heist | 1903 |
| Portion | | | E. Bird & A. Nelson | 1944 |
| Portion | | | J.L. Thomas | 1987 |
| SOUTH BOUNDARY | | | | |
| Portion | A.J. Stewart, Jr. | 1878 | | |
| Portion | Stewart & Stewart | 1898 | | |
| Portion | | | E. Bird & A. Nelson | 1944 |
| Portion | | | A. Zaninovich | 1991 |
| EAST BOUNDARY | | | | |
| All | A.J. Stewart, Jr. | 1878 | | |
| WEST BOUNDARY | | | | |
| Portion | J. Gorkinski | 1873 | | |
| All | E. Bird & A. Nelson | 1944 | E. Bird & A. Nelson | 1944 |
| SUBDIVISION | | | | |
| Portion | A.J. Stewart, Jr. | 1878 | | |
| Portion | E. Bird & A. Nelson | 1944 | E. Bird & A. Nelson | 1944 |

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973; and the Special Instructions dated September 6, 1996, for Group No. 857, Utah.

Preliminary to the resurvey, a diligent search was made for any evidence of the original field note record. Coordinates by the use of Global Positioning System (G.P.S.) equipment were determined for each found and proportioned corner in this survey. True bearings and distances were calculated by inverting between these points.

TOWNSHIP 12 SOUTH, RANGE 2 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The geographic position of the 1/4 section corner of sections 6 and 31, Tps. 12 and 13 S., R. 2 W., which will also function as a B.L.M. control station, was determined by G.P.S. methods, from U.S. Coast & Geodetic Survey Triangulation Station "CAPPS", is as follows:

Latitude 39° 42' 55.452" N. Longitude 112° 05' 21.179" W.
N.A.D. 1927.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 13 3/4° E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 S. R. 2 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.J. Stewart, Jr., in 1878

Beginning at the corner of sections 16, 17, 20, and 21, monumented with a granite stone, 30x12x8 ins., set in a small mound of stone, dimly marked with 3 notches on the S edge and 4 notches on E edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

| | |
|------|------|
| T12S | R2W |
| S 17 | S 16 |
| S 20 | S 21 |
| 1996 | |

Bury the rock corner in base of mound of stone.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 43.0' W., between sections 16 and 17.

40.084

Point for the 1/4 section corner of sections 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R2W

1/4

S 16 | S 17

1996

Raise a mound of stone west of aluminum post.

80.168

The corner of sections 8, 9, 16, and 17, monumented with a trachyte stone, 20x15x8 ins., dimly marked, with 4 notches on the S and E edges, and in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top of aluminum cap marked:

T12S R2W

S 8 | S 9

S 17 | S 16

1996

Bury the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 1° 09.1' W., between sections 8 and 9.

20.063

Point for the S 1/16 section corner of sections 8 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap marked:

T12S R2W

S 1/16

S 8 | S 9

1996

40.126

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock, and in a mound of stone, with a 6 ft. base, to top of aluminum cap marked:

T12S R2W

1/4

| | |
|-----|-----|
| S 8 | S 9 |
|-----|-----|

1996

80.252

The corner of sections 4, 5, 8, and 9, monumented with a trachyte stone, 18x10x10 ins., firmly set and plainly marked 4 notches on the E edge and 5 notches on the S edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W

| | |
|-----|-----|
| S 5 | S 4 |
|-----|-----|

| | |
|-----|-----|
| S 8 | S 9 |
|-----|-----|

1996

Bury the corner stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

Reestablishment of the Survey Executed by A.J. Stewart, Jr.,
in 1878 and the Resurvey by E. Bird and A. Nelson in 1944

From the corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., 6 ins. above ground, 4 ft. base, 1 ft. high, mound of stone, west of corner, with a brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 59.8' W., bet. sections 30 and 31.

19.998

Point for the E 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

| | |
|--------|----------|
| | T12S R2W |
| | S30 |
| E 1/16 | _____ |
| | S31 |
| | 1996 |

Set a 6 ft. steel fence post alongside the aluminum post.

39.996

The 1/4 section corner of sections 30 and 31, monumented with an iron post, 1 in. diam., 8 ins. above ground, in a collar of stone, with brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

From the 1/4 section corner of sections 29 and 30, monumented with an iron post, 1 in. diam., in a mound of stone, 4 ft. base, 1 ft. high, to top of brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 58.2' W., bet. sections 29 and 30.

20.149

Point for the N 1/16 section corner of sections 29 and 30; not monumented.

40.298

The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam. with brass cap marked as described in the official record of the 1944 resurvey.

N. 89° 58.8' W., bet. sections 19 and 30.

20.008

Point for the E 1/16 section corner of sections 19 and 30; not monumented.

40.016

The 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 in. diam., 12 ins. above ground, with; brass cap marked as described in; the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 19 and 20, monumented with an iron post, 1 in. diam., in a mound of stone, 3 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

N. 1° 07.8' W., bet. sections 19 and 20.

20.038

Point for the N 1/16 section corner of sections 19 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
N 1/16
S 19 | S 20
1996

Set a 6 ft. steel fence post alongside the aluminum post.

An east and west fence line is north of corner.

40.076

The corner of sections 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., in a mound of stone, with 6 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

From the corner of sections 16, 17, 20, and 21.

S. 89° 12.4' W., between sections 17 and 20.

39.359

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T12S R2W
1/4 S17
S20
1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

78.718 The corner of sections 17, 18, 19, and 20.

N. 89° 58.8' W., bet. sections 18 and 19.

20.007 Point for the E 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with aluminum cap marked:

| | |
|--------|-----------|
| | T12S R2W |
| | S18 |
| E 1/16 | <hr/> S19 |
| | 1996 |

Set a 6 ft. steel fence post alongside the aluminum post.

40.014 The 1/4 section corner of sections 18 and 19, monumented with an iron post, 1 in. diam., in a mound of stone, with brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

From the corner of sections 17, 18, 19, and 20.

N. 1° 13.7' W., bet. sections 17 and 18.

19.758 Point for the S 1/16 section corner of sections 17 and 18, not monumented.

39.516 The 1/4 section corner of sections 17 and 18, monumented with an iron post, 1 in. diam., in a mound of stone, with a 5 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

N. 1° 13.8' W., beginning new measurement.

39.558 The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., 6 ins. above ground, and in a collar of stone, with brass cap marked as described in the official record of the 1944 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in an E and W fence line.

From the corner of sections 8, 9, 16, and 17.

S. 88° 25.0' W., bet. sections 8 and 17.

39.708

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, with 4 ft. base, to top of aluminum cap marked:

T12S R2W

S8

1/4

S17

1996

59.562

Point for the W 1/16 section corner of sections 8 and 17; not monumented.

79.416

The corner of sections 7, 8, 17, and 18.

S. 89° 57.9' W., bet. sections 7 and 18.

40.020

The 1/4 section corner of sections 7 and 18, monumented with an iron post, 1 in. diam., in a mound of stone, with 4 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the iron post.

From the corner of sections 7, 8, 17, and 18.

N. 1° 13.6' W., bet. sections 7 and 8.

20.090

Point for the S 1/16 section corner of sections 7 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R2W

S 1/16

S 7 | S 8

1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.180

The 1/4 section corner of sections 7 and 8, monumented with an iron post, 1 in. diam., in a mound of stone, with 4 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 1° 06.8' W., beginning new measurement.

39.568

The corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., in a mound of stone, 5 ft. base, to top of brass cap marked as described in the official record of the 1944 resurvey.

From the corner of sections 4, 5, 8, and 9.

S. 88° 03.2' W., bet. sections 5 and 8.

39.717

Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, with 3 ft. base, to top of aluminum cap marked:

T12S R2W

S5

1/4

S8

1996

Set a 6 ft. steel fence post alongside the aluminum post.

79.434

The corner of sections 5, 6, 7, and 8.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. $89^{\circ} 58.0'$ W., bet. sections 6 and 7.

40.053

The $1/4$ section corner of sections 6 and 7, monumented with an iron post, 1 in. diam., firmly set and exposed 6 ins. above ground, with brass cap marked as described in the official record of the 1944 resurvey.

Set a 6 ft. steel fence post alongside the iron post.

Corner is located 10 lks. N of a fence line bearing E and W.

The Subdivision of Section 7,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the $1/4$ section corner of sections 7 and 18.

N. $1^{\circ} 12.0'$ W., on the N-S center line of section 7.

19.994

Point for the center S $1/16$ section corner of section 7.

Set an aluminum post, 30 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, in a mound of stone, to top of aluminum cap marked:

| | | | |
|---|--------|---|-----|
| | T12S | | R2W |
| | | C | |
| S | $1/16$ | | S 7 |
| | | C | |

1996

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the corner.

39.988

Point for the center $1/4$ section corner of section 7, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | | | |
|---|-------|--|-----|
| | T12S | | R2W |
| C | $1/4$ | | S 7 |

1996

THE SUBDIVISION OF SECTION 7,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

79.744 The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

S. 89° 41.9' W., on the E-W center line of section 7.

39.992 The center 1/4 section corner of section 7.

71.896 The 1/4 section corner of section 7 only, on the west boundary of the township, monumented with an iron post, 1 in. diam., in a mound of stone, 5 ft. base, to top of brass cap marked as described in the official record of the 1944 survey.

Set a 6 ft. steel fence post alongside the iron post.

From the S 1/16 section corner of sections 7 and 8.

S. 89° 49.9' W., on the E-W center line of the SE 1/4 of section 7.

40.006 The center S 1/16 section corner of section 7.

The Subdivision of Section 8,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 1° 09.7' W., on the N-S center line of section 8.

20.077 Point for the center S 1/16 section corner of section 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 8,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R2W

C
 $\left| \begin{array}{cc} S \ 1/16 & S \ 8 \end{array} \right.$
 C

1996

40.154 Point for the center 1/4 section corner of section 8, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W

C 1/4 S 8

1996

Set a 6 ft. steel fence post alongside the aluminum post.

80.000 The 1/4 section corner of sections 5 and 8.

From the 1/4 section corner of sections 8 and 9.

S. 88° 27.4' W., on the E-W center line of section 8.

39.711 The center 1/4 section corner of section 8.

59.587 Point for the center W 1/16 section corner of section 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
 C $\frac{W \ 1/16}{S8}$ C
 1996

Set a 6 ft. steel fence post alongside the aluminum post.

79.463 The 1/4 section corner of sections 7 and 8.

THE SUBDIVISION OF SECTION 8,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the S 1/16 section corner of sections 8 and 9.
- S. 88° 26.2' W., on the E-W center line of the SE 1/4 of section 8.
- 39.710** The center S 1/16 section corner of section 8.
-
- From the point for the W 1/16 section corner of sections 8 and 17; not monumented.
- N. 1° 11.7' W., on the N-S center line of the SW 1/4 of section 8.
- 20.084** Point for the SW 1/16 section corner of section 8, at intersection with the E-W center line of the SW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T12S R2W
SW 1/16
S 8
1996
- Set a 6 ft. steel fence post alongside the aluminum post.
- 40.168** The center W 1/16 section corner of section 8.
-
- From the center S 1/16 section corner of section 8.
- S. 88° 26.2' W., on the E-W center line of the SW 1/4 of section 8.
- 19.865** The SW 1/16 section corner of section 8.
- 39.730** The S 1/16 section corner of sections 7 and 8.
-
- The Subdivision of Section 18,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 18 and 19.
- N. 1° 14.3' W., on the N-S center line of section 18.
- 19.762** Point for the center S 1/16 section corner of section 18.

THE SUBDIVISION OF SECTION 18,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, to top of aluminum cap marked:

T12S R2W
C
S 1/16 S 18
C

1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.524 Point for the center 1/4 section corner of section 18, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
C 1/4
S 18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

79.036 The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

N. 89° 58.1' W., on the E-W center line of section 18.

20.009 Point for the center E 1/16 section corner of section 18; not monumented.

40.018 The center 1/4 section corner of section 18.

73.652 The 1/4 section corner of section 18 only, on the west boundary of the township, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1944 survey.

THE SUBDIVISION OF SECTION 18,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the E 1/16 section corner of sections 18 and 19.

N. 1° 14.0' W., on the N-S center line of the SE 1/4 of section 18.

19.760 Point for the SE 1/16 section corner of section 18, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, with 6 ft. base to top of aluminum cap marked:

T12S R2W
SE 1/16
S 18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.520 The point for the center E 1/16 section corner of section 18; not monumented.

From the point for the S 1/16 section corner of sections 17 and 18; not monumented.

N. 89° 58.4' W., on the E-W center line of the SE 1/4 of section 18.

20.008 The SE 1/16 section corner of section 18.

40.016 The center S 1/16 section corner of section 18.

The Subdivision of Section 19,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30.

N. 0° 53.9' W., on the N-S center line of section 19.

39.991 Point for the center 1/4 section corner of section 19, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
C 1/4
S 19
1996

THE SUBDIVISION OF SECTION 19,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

60.008 Point for the center N 1/16 section corner of section 19; not monumented.

80.025 The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20.

N. 89° 55.4' W., on the E-W center line of section 19.

20.090 Point for the center E 1/16 section corner of section 19; not monumented.

40.180 The center 1/4 section corner of section 19.

75.350 The true point for the 1/4 section corner of section 19 only, on the west boundary of the township. From this true point, the witness 1/4 section corner bears North, 0.130 chs. dist., monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1944 survey.

From the point for the center E 1/16 section corner of section 19; not monumented.

N. 1° 00.9' W., on the N-S center line of the NE 1/4 of section 19.

20.027 Point for the NE 1/16 section corner of section 19, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
NE 1/16
S 19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.054 The E 1/16 section corner of sections 18 and 19.

From the N 1/16 section corner of sections 19 and 20.

N. 89° 57.1' W., on the E-W center line of the NE 1/4 of section 19.

20.049 The NE 1/16 section corner of section 19.

40.098 The point for the center N 1/16 section corner of section 19; not monumented.

THE SUBDIVISION OF SECTION 30,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 30,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. 0° 56.7' W., on the N-S center line of section 30.

40.354 Point for the center 1/4 section corner of section 30, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
C 1/4
S 30
1996

Set a 6 ft. steel fence post alongside the aluminum post.

60.517 Point for the center N 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
C
N 1/16 | S 30
C

1996

Set a 6 ft. steel fence post alongside the aluminum post.

80.680 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

S. 89° 59.0' W., on the E-W center line of section 30.

20.018 Point for the center E 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 30,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R2W
C $\frac{E 1/16}{S 30}$ C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.036 The center 1/4 section corner of section 30.

76.518 The 1/4 section corner of section 30 only, on the west boundary of the township, monumented with an iron post, 1 in. diam., in a mound of stone, 5 ft. base, to top of brass cap marked as described in the official record of the 1944 survey.

From the center E 1/16 section corner of section 30.

N. 0° 57.4' W., on the N-S center line of the NE 1/4 of section 30.

20.156 Point for the NE 1/16 section corner of section 30, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T12S R2W
NE 1/16
S 30
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.312 The point for the E 1/16 section corner of sections 19 and 30; not monumented.

From the point for the N 1/16 section corner of sections 29 and 30; not monumented.

N. 89° 59.9' W., on the E-W center line of the NE 1/4 of section 30.

20.013 The NE 1/16 section corner of section 30.

40.026 The center N 1/16 section corner of section 30.

From the E 1/16 section corner of sections 30 and 31.

N. 0° 54.8' W., on the N-S center line of the SE 1/4 of section 30.

40.358 The center E 1/16 section corner of section 30.

THE SUBDIVISION OF SECTION 31,
T. 12 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 31,
T. 12 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 6 and 31, on the south boundary of the township, monumented with an iron post, 1 in. diam., 12 ins. above ground, in a collar of stone, with brass cap marked as described in the official record of the 1944 survey.

Corner falls in N and S fence line.

N. 2° 04.2' W., on the N-S center line of section 31.

37.801 Point for the center 1/4 section corner of section 31, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R2W
C 1/4
S 31
1996

Set a 6 ft. steel fence post alongside the aluminum post.

77.153 The 1/4 section corner of sections 30 and 31.

From the 1/4 section corner of sections 31 and 32, monumented with an iron post, 1 in. diam., 8 ins. above ground, in a collar of stone, with brass cap marked as described in the official record of the 1944 resurvey.

N. 88° 46.9' W., on the E-W center line of section 31.

39.152 The center 1/4 section corner of section 31.

77.778 The 1/4 section corner of section 31 only, on the west boundary of the township, monumented with an iron post, 1 in. diam., 8 ins. above ground, in a collar of stone, with brass cap marked as described in the official record of the 1944 survey.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| Name | Capacity |
|--|----------------------|
| Steven Oatman | Surveying Technician |
| Nathan James | Survey Aid |
| Tracy Thompson (Bureau of Reclamation) | Survey Aid |

CERTIFICATE OF SURVEY

We, *M. Ross Workman and Ronald K. Baugh*, *Supervisory Cadastral Surveyors*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *6th day of September, 1996*, we have *dependently resurveyed a portion of the subdivisional lines and subdivided sections 7, 8, 18, 19, 30, and 31, in Township 12 South, Range 2 West*,

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 16, 1998

Date

March 16, 1998

Date

M. Ross Workman

(Cadastral Surveyor)

Ronald K. Baugh

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 7, 8, 18, 19, 30, and 31, Township 12 South, Range 2 West, Salt Lake Meridian, Utah*,

executed by *M. Ross Workman and Ronald K. Baugh*, *Supervisory Cadastral Surveyors*

having been critically examined and found correct, are hereby approved.

March 18, 1998

Date

Daniel W. Wehler

(Chief Cadastral Surveyor for Utah)